



LISTING INFORMATION OF  
**Eurodek Plus 65 mil Roofing Membranes**  
SPEC ID: 33165

Eurodek Products  
602 Adams Rd.  
Kelowna, BC V1X 7S1  
Canada

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program.

## LISTING INFORMATION

Eurodek "PLUS" - 65 mil

Eurodek PLUS is a flexible polyvinylchloride (PVC) membrane made with a nominal thickness of 65 mil (1.5 mm). The product is made with a heat set non-woven polyester backing. The surface of membrane is embossed to provide a textured finish. The membrane is available in rolls that are 54 inches (1372 mm) or 72 inches (1829 mm) in width and can be cut to required length. The product is available in a variety of colours and print patterns.

<b>Attribute</b>	<b>Value</b>
Criteria	CAN / CGSB 37.54 (1995)
Criteria	ASTM D4434 (2015)
CSI Code	07 50 00 Membrane Roofing
Intertek Services	Certification
Listed or Inspected	LISTED
Listing Section	ROOFING MATERIALS
Spec ID	33165